Lead Lined PET Unit Dose Cabinet / Table



- Designed for PET hot labs with limited space
- Accommodates:
- Compact L-Block with Built-in Dose Calibrator Shield (042-433)
- PET Sharps Container Shield (039-412)
- Lead Brick Cave (042-434)
- Atomlab Dose Calibrators and most others
- Sliding shelves for:
- PET shipping containers
- Small items
- Lead shielded on all six sides
- · Key-locked doors

Upon request, the manufacturer will factory mount the L-Block and Sharps Shield in place, eliminating the need for on-site lifting equipment. A simple pallet jack is all that is required to move the unit.

Specifications:

Dimensions: 36.5" W x 24" D x 36.5" H

Lead Shielding: 1/4" thick
Finish: Powder coat
Doors: Key-locked

Countertop: Stainless steel with 4" backsplash and

1/2" spillproof lip

Weight Capacity: 1550 lb Weight: 1240 lb

Accommodates lead brick cave 042-434

244-205 PET Unit Dose Cabinet, 1/4" lead

244-206 PET Unit Dose Cabinet, 1/2" lead

244-207 PET Unit Dose Cabinet, 1" lead

Does not accommodate lead brick cave

244-201 PET Unit Dose Cabinet, 1/2" Lead

244-202 PET Unit Dose Cabinet, 1" Lead

Standard Configuration:

042-433 Compact L-Block Shield, 1.5" lead

With built-in Dose Calibrator Shield

042-434 3-wall Lead Brick Cave, 2" lead

Fits: 042-433 L-Block Shield

5730-2271 PET Sharps Container Shield, 1" lead

Uses one NMC-416 Sharps Container

NMC-416 3.2 quart Sharps Container, 12/pkg



- Designed for PET hot labs with limited space
- Lead shielding under calibration chamber
- Ships Completely Assembled:
 - Compact L-Block Shield with Built-in Dose Calibrator Shield (042-433)
 - PET Sharps Container Shield (039-412)
- Shelf space for:
 - PET shipping containers
 - Small items

Ships completely assembled, the Unit Dose Table eliminates the need for on-site lifting equipment. A simple pallet jack is all that is required to move the unit.

Specifications:

042-448 PET Unit Dose Table:

Dimensions: 36.75" W x 24" D x 36" H

Front legs incorporate adjustable levelers

Lead Shielding: 1" thick (enclosed in chamber mounting shelf)

Finish: Powder coat Weight Capacity: 1550 lb Weight: 294 lb

042-433 Compact L-Block with Dose Calibrator Shield:

Dimensions: 18" W x 21.5" D x 26" H Lead Shielding: Front: 1.5" thick

Base: 1" thick Calibrator Shield: 1" thick

Calibrator Shield: I.D.: 6.85" I.D. x 10.25" H

Lead Glass Window:

Dimensions: 8" W x 8" H x 4" thick

Density: 5.2 g/cm³

Finish: Powder coat Weight: 590 lb

5730-2271 PET Sharps Container Shield:

Dimensions: 13.5" H x 10.6" Diameter Lead Shielding: Sides and Bottom: 1" thick

Security: Key-locked Weight: 160 lb

042-448 PET Unit Dose Table

 $Includes: 042-433\ Compact\ L\text{-}Block\ with$

Dose Calibrator Shield and 5730-2271

Sharps Container Shield

042-434 3-wall Lead Brick Cave, 2" lead

Fits: 042-433 L-Block Shield

5730-2271 PET Sharps Container Shield, 1" lead

Uses one NMC-416 Sharps Container

NMC-416 3.2 quart Sharps Container, 12/pkg