

Lead-Lined Storage Safe



- Stainless steel 2" lead-lined safe
- Key locked door
- This unit can be moved with a pallet jack
- Adjustable heavy duty shelf

Specifications:

Outer Dimensions: 17 1/2" W x 17 1/2" D x 22" H
 Inner Dimensions: 13.5" W x 14" D x 14.5" H
 Shielding: 2" lead on all 6 sides
 Door latch: Key-locked
 Weight: 1,435 lbs

PTI-006

Lead-Lined Storage Safe, 2" lead

Lead-Lined Refrigerator

- Laboratory quality refrigerator for uniform temperature operation
- Digital microprocessor LED control with automatic tracking alarms and remote alarm contacts
- Three adjustable wire shelves
- Front to back breathable airflow design for low maintenance and no side or top clearance requirements



Specifications:

Outer Dimensions: 23.6" W x 26.2" D x 34.6" H
 Lead Shielding: 1/8", 1/4" or 1/2"
 Capacity: 6.1 cu ft
 Temperature: 1° C to 14° C
 Door: Key-locked
 Finish: Stainless Steel
 Power: 115V / 60 Hz

Specifications Subject to Change

LLR-18

Lead-Lined Refrigerator, 1/8" lead, Wt. 290 lbs. Shipping Wt. 340 lbs

LLR-14

Lead-Lined Refrigerator, 1/4" lead, Wt. 440 lbs. Shipping Wt. 490 lbs

LLR-12

Lead-Lined Refrigerator, 1/2" lead, Wt. 770 lbs. Shipping Wt. 820 lbs

Decay Cabinet on Casters

- Short term and long term storage compartments
- Slide out tray
- Front and top openings
- Lockable doors
- Stainless steel inside and outside (no exposed lead)

Specifications:

External Dimensions: 30"W x 16"D x 29.5"T

Weight: 1/4" Lead - 445 lbs

1/2" Lead - 800 lbs

3/4" Lead - 1150 lbs



DC-014

Decay Cabinet on Casters, 1/4" Lead

DC-012

Decay Cabinet on Casters, 1/2" Lead

DC-034

Decay Cabinet on Casters, 3/4" Lead